

PMX

HEAVY DUTY OIL



PMX TRUCK

HD engine oil.
For trucks and vans, buses, agricultural
and construction machinery,
stationary engines, etc.



TRUCK 10W-30 EHP FE

PMX Truck 10W-30 EHP FE - Semi-synthetic engine oil
with Low SAPS technology:

- Recommended for machines with DPF / SCR / EGR.
- Recommended for machines under heavy and demanding use.
- Very low pour point, good cold start properties.
- Very good anti-wear properties.
- Suitable for long shift intervals.
- High TBN level.

Search ID: PMXT13EHPFE		
20 L	205 L	1000



Specifications

API CK-4; ACEA E7, E8, E11; DTRF 15C120, 15C110 (228.52, 228.51); MAN M3775; Deutz DQC IV-18 LA; Volvo VDS-4.5; Mack EOS-4.5; Renault VI RLD-3; MTU Type 3.1, 2.1; Cummins CES 20086, CES 20092; Detroit Diesel DFS 93K222; Caterpillar ECF-3; JASO DH-2



TRUCK 10W-40 E7

PMX Truck 10W-40 E7 - Mineral oil with a strong
additive package:

- Recommended for machines with Euro V and SCR.
- Recommended for machines under heavy and demanding use.
- Low pour point, good cold start properties.
- Very good anti-wear properties.
- Suitable for trucks, buses, agriculture and construction equipment.
- Suitable for Euro I, II, III, IV & V.

Search ID:
PMXT1040E7

20 L	205 L	1000
-------------	--------------	-------------



Specifications

API CI-4, CF, SL; ACEA E7, E5; Mercedes MB 228.3; MAN M 3275; Volvo VDS-3; MTU type 2; Mack EO-N; Renault RLD-2



TRUCK 10W-40 LD E11

PMX Truck 10W-40 LD E11 - Semi-synthetic engine oil
with Low SAPS technology:

- Recommended for machines with DPF /SCR / EGR.
- Recommended for machines under heavy and demanding use.
- Very low pour point, good cold start properties.
- Very good anti-wear properties.
- Suitable for long shift intervals.
- High TBN level.

Search ID:
PMXT14LDE11

20 L	205 L	1000
-------------	--------------	-------------



Specifications

API CK-4, SL; ACEA E4, E7, E8, E11; MAN M3477, M3775, M3271-1; DTRF 15C120, 15C110, 15C100 (228.52, 228.51, 228.31); Volvo VDS-4.5; Renault VI RLD-4, RLD-3; Scania LA; Mack EOS-4.5; MTU Type 3.1, Type 2.1; Deutz DQC-IV-18 LA; Detroit Diesel 93K222; Cummins CES 20086, CES 20081; Caterpillar ECF-3; JASO DH-2



TRUCK 15W-40 E7

PMX Truck 15W-40 E7 - Semi-synthetic oil with a strong additive package:

- Recommended for machines with and without Turbo.
- Recommended for machines under heavy and demanding use.
- Low pour point, good cold start properties.
- Very good anti-wear properties.
- Suitable for trucks, buses, agriculture and construction equipment.
- Suitable for Euro I, II, III, IV & V.

Search ID:
PMXT1540E7

20 L	205 L	1000
------	-------	------



Specifications

ACEA E7; API CI-4, SL; Cat ECF-1-a, ECF-2; Cummins CES 20077, 20078; Detroit Diesel 93K215; Deutz DQC III-18; DTFR 15B110; Global DHD-1; JASO DH-1; Mack EO-N, EO-M Plus; MAN M 3275-1; Mercedes MB 228.3; MTU Type 2; Renault VI RLD-2; Volvo VDS-3; Allison C3, CAT TO-2; ZF 04C, 04P, 07C, 07D, 21K



TRUCK 15W-40 EHP

PMX Truck 15W-40 EHP - Semi-synthetic engine oil with Low SAPS technology:

- Recommended for machines with DPF /SCR / EGR.
- Recommended for machines under heavy and demanding use.
- Very low pour point, good cold start properties.
- Very good anti-wear properties.
- Suitable for long shift intervals.
- High TBN level.

Search ID:
PMXT24EHP

20 L	205 L	1000
------	-------	------



Specifications

ACEA E7, E9, E11; API CK-4, SN; Cat ECF-3; Cummins CES 20086; Detroit Diesel 93K222; Deutz DQC III-18 LA; DTFR 15C100; Ford M2C171-F1; JASO DH-2; Mack EOS-4.5; MAN M 3775; Mercedes MB 228.31; MTU Type 2.1; Renault VI RLD-3; Volvo VDS-4.5; Allison TES-439



TRUCK 5W-30 LD FE E11

PMX Truck 5W-30 LD FE E11 synthetic engine oil with Low SAPS technology:

- Recommended for machines with DPF/SCR/EGR.
- Recommended for machines under heavy and demanding use.
- Very low pour point, good cold start properties.
- Very good anti-wear properties.
- Suitable for long shift intervals.
- High TBN level.

Search ID:
PMXT53LFE11

20 L	205 L	1000
------	-------	------



Specifications

API CK-4, SL; ACEA E4, E7, E8, E11; MAN M3777, M3677, M3775, M3477, M3271-1; DTFR 15C120, 15C110, 15C100 (228.52, 228.51, 228.31); MTU Type 3.1, Type 2.1; Deutz DQC IV-18 LA; Volvo VDS-4.5; Renault VI RLD-4, RLD-3; Scania LDF-4; Mack EOS-4.5; Caterpillar ECF-3; Cummins CES 20086, CES 20081; JASO DH-2, DH-1, DL-0; Detroit Diesel 93K218, 93K222



TRUCK 5W-30 VDS-5

PMX Truck 5W-30 VDS-5 synthetic engine oil with Low SAPS technology:

- Recommended for machines with DPF/SCR/EGR.
- Prevents the formation of particles and sludge in the oil.
- Very low pour point, good cold start properties.
- Reduces wear on piston rings and cylinder polishing.
- Provides improved fuel economy.
- Contributes to lower maintenance costs.

Search ID:
PMXT53V

20 L	205 L	1000
------	-------	------



Specifications

ACEA F01; API FA-4, SN Plus; DTFR 15C130; Mack EOS-5; Renault RLD-5; Volvo VDS-5; Cummins CES 20087; Detroit Diesel DFS 93K223; Ford M2C214-B1; JASO DH-2; Mercedes MB 228.61

PMX MULTI/WET BRAKE

Multi-purpose oils.
For agricultural and construction machinery
with wet rear brakes

PMX

MULTI 10W-30 STOU

PMX Multi 10W-30 STOU - Universal engine/gear and hydraulic oil:

- Can be used for wet brakes and Limited-Slip systems.
- Very good protection against wear, corrosion and foam.
- Very low pour point, good cold start properties.
- Very good anti-wear properties.
- Good water separation properties.
- High and stable viscosity index.

Search ID:
PMXM1030S

20 L	205 L	1000
------	-------	------



Specifications

API CG-4; API GL-4; ACEA E3; ISO: HV; DIN: HVLP;
John Deere JDM J27; Massey Ferguson CMS M1145, M1144,
M1139; Ford M2C159B; ZF 06A, 06B, 06C, 06D, 07B;
New Holland 82009201, 2, 3; Allison C-4; Caterpillar TO-2;
Mercedes MB 228.1, 227.1; MAN 271

PMX

MULTI 10W-40 STOU

PMX Multi 10W-40 STOU - Universal engine/gear and Hydraulic Oil:

- Can be used for wet brakes and Limited-Slip systems.
- Very good protection against wear, corrosion and foam.
- Very low pour point, good cold start properties.
- Very good anti-wear properties.
- Good water separation properties.
- High and stable viscosity index.

Search ID:
PMXM1040S

20 L	205 L	1000
------	-------	------



Specifications

API CG-4; API GL-4; ACEA E3; ISO: HV; DIN: HVLP;
John Deere JDM J27; Massey Ferguson CMS M1145, M1144,
M1139; Ford M2C159B; ZF 06A, 06B, 06C, 06D, 07B;
New Holland 82009201, 2, 3; Allison C-4; Caterpillar TO-2;
Mercedes MB 228.1, 227.1; MAN 271

PMX

WB UTTO

PMX WB UTTO 10W-30 - GL-4/ HVLP:

- Good resistance to high temperatures and heavy loads.
- Suitable for use on wet brake systems.
- Low pour point.
- Suitable for hydraulic/gear systems.
- Contains LS additive.
- High viscosity index.

Search ID:
PMXWBU

20 L	205 L	1000
------	-------	------



Spekifikationer

API GL-4; ISO: HV; DIN: HVLP; John Deere JDM J20C, J20D;
Case New Holland MAT 3540, 3526, 3525, 3505;
Case MS 1210, 1209, 1207;
Ford M2C86B, M2C86C, M2C134-D, FNHA-2-C-200, FNHA-
2-C-201; Massey Ferguson CMS M1145, M1143, M1141, M1135;
Volvo WB-101; Caterpillar TO-4; Allison C-4;
ZF 03E, 03F, 05F, 06E, 06K, 17E, 21F



WB UTTO SYN

PMX WB UTTO SYN:

- Good resistance to high temperatures and loads.
- Suitable for use on wet brake systems.
- Low pour point.
- Suitable for hydraulic/gear systems.
- Contains LS additive.
- High viscosity index.

Search ID:
PMXWBUS

20 L	205 L	1000
------	-------	------



Specifications

API GL-4; Allison C4; Case MS1207, MS1209; Cat TO-2; John Deere J20A; Massey Ferguson M1141, M1143, M1145; Volvo WB 102; Volvo 97304; ZF 03E, 06K



WB UTTO TO-4

PMX WB UTTO TO-4 - Powershift transmission:

- Good resistance to high temperatures and loads.
- Suitable for use on wet brake systems.
- Low pour point.
- Suitable for hydraulic/gear systems.
- Protects against corrosion.

Search ID:
PMXWBUT4

20 L	205 L	1000
------	-------	------



Specifications

API GL-4; Allison C4; Cat TO-4, TO-2; Komatsu KES 07.868.1; ZF 03C; Eaton (Vickers) M-2950-S / I-286-S



ATF / GEAR

For automatic and manual transmissions, as well as power-steering gear



ATF DEXRON III

PMX ATF Dexron III H - Semi-synthetic automatic transmission oil:

- Good resistance to oxidation.
- Very good protection against wear, corrosion and foam.
- Low pour point.
- Tuned frictional properties.
- Very high and stable viscosity index.
- Red dye.

Search ID:
PMXAD3

20 L	205 L	1000
------	-------	------



Specifications

Dexron IIIH (Dexron IIIG, IIIF, IIE, IID); Ford Mercon; Caterpillar TO-2; Allison C4, Allison TES 389; Ford M2C138-CJ, M2C166-H; Mercedes MB 236.1 /236.3 /236.5 / 236.6 /236.7/ 236.9 / 236.10 / 236.93; DTFR 13C100 / 13C140 / 13C170 / 13B100; MAN 339 Typ Z1/V1 / Z2; Volvo 97340 /97341 / AT101; ZF 02F, 03D, 04D, 14B, 16L, 17C; Voith G.607, H 55.6336.41

PMX GEAR

For transmissions and hypoid differentials in passenger cars, vans and trucks



GEARBOX OIL 75W-90 GL-4/5

PMX Gearbox oil 75W-90 GL-4/5 - Synthetic gear oil:

- Good resistance to oxidation.
- Very good protection against wear, corrosion and foam.
- Low pour point.
- Very good EP properties.
- High viscosity index.

Search ID: PMXGO79G45		
20 L	60 L	205 L
1000		



Specifications

API GL-3, -4, -5, MT-1; MIL-L-2105D, MIL-PRF-2105E, SAE J2360, DAF; DTFR 12B140, Iveco; Mack GO-J, MAN 341 Typ Z2, 342 Typ M3; Mercedes MB 235.8, 235.9; Scania STO 1:0; Volvo 97312; ZF 02B, 05A, 07A, 12L, 12N, 16B, 16F, 17B, 19C, 21A



GEARBOX OIL 75W-90 GL-5 LS

PMX Gearbox oil 75W-90 GL-5 LS - Very high quality full synthetic gear oil:

- Good resistance to high temperatures and loads.
- Very good protection against wear, corrosion and foam.
- Low pour point.
- Very good EP properties.
- Contains LS additive.
- High viscosity index.

Search ID: PMXGO79G55		
20 L	205 L	1000



Specifications

API GL-4, -5, MT-1; MIL-L-2105D/MIL-PRF-2105E, SAE J2360; MAN 341 Typ Z2, 342 Typ S1; MAN 3343 Typ S; Scania STO 1:0; Volvo 97310; ZF 05C, 07A, 12B, 12L, 12N, 16B, 16F, 17B, 19C, 21C



TRUCK GEAR OIL 75W-140

PMX Truck Gear Oil 75W-140 with EP Features:

- Good resistance to oxidation.
- Very good protection against wear, corrosion and foam.
- Very low pour point.
- Very good EP properties.
- High viscosity index.

Search ID: PMXTGO71		
20 L	205 L	1000



Specifications

API GL-5; MIL-L-2105D; ZF 05B, 07A, 08, 12B, 16F, 19C, 21A



TRUCK GEAR OIL 80W-90 GL-5

PMX Truck Gear Oil 80W-90 GL-5 with EP features:

- Good resistance to oxidation.
- Very good protection against wear, corrosion and foam.
- Very low pour point.
- Very good EP properties.
- High viscosity index.

Search ID:
PMXGO89G

20 L 205 L 1000



Specifications

API GL-5; Mercedes MB 235.0; MIL-L-2105D; MAN 342 Type M1; ZF 07A, 16B-D, 17B, 19B; Voith 3.325-339; Volvo 97310, Volvo 97316; DAF



TRUCK GEAR OIL SAE 90 GL-5 LS

PMX Truck Gear Oil SAE 90 GL-5 LS with EP features:

- Good resistance to high temperatures and loads.
- Very good protection against wear, corrosion and foam.
- Low pour point.
- Very good EP properties.
- Contains LS additive.
- High viscosity index.

Search ID:
PMXGOS9G

20 L 205 L 1000



Specifications

API GL-5 LS; MIL-L-2105D; Volvo 97310; ZF 05C, 12C, 16E, 21C



TRUCK GEAR OIL 75W-90 GL-5

PMX Truck Gear Oil 75W-90 GL-5:

- Good resistance to oxidation.
- Very good protection against wear, corrosion and foam.
- Very low pour point.
- Very good EP properties.
- High viscosity index.

Search ID:
PMXG79G5

20 L 205 L 1000



Specifications

API GL-5; MIL-L-2105D; ZF 5A, 7A, 8A, 16B-D, 17B



TRUCK GEAR OIL 75W-90 GL-5 LS

PMX Truck Gear Oil 75W-90 GL-5 LS:

- Good resistance to high temperatures and loads.
- Very good protection against wear, corrosion and foam.
- Low pour point.
- Very good EP properties.
- Contains LS additive.
- High viscosity index.

Search ID:
PMXG79G5LS

20 L 205 L 1000



Specifications

API GL-5 LS; MIL-L-2105D



80W-90 LS

PMX 80W-90 LS with EP properties:

- Good resistance to high temperatures and loads.
- Very good protection against wear, corrosion and foam.
- Low pour point.
- Very good EP properties.
- Added LS additive.
- High viscosity index.

Search ID: PMX89LS		
20 L	205 L	1000



Specifications
API GL-5; API GL-5 LS



85W-140 G5

PMX 85W-140 G5 with EP features:

- Good resistance to oxidation.
- Very good protection against wear, corrosion and foam.
- Very low pour point.
- Very good EP properties.
- High viscosity index.

Search ID: PMX140G5		
5 L	20 L	205 L
1000		



Specifications
API GL-5; MIL-L-2105D; ZF 07A, 21A



GEARBOX OIL 75W-140

PMX Gearbox Oil 75W-140 - High quality full-synthetic gear oil:

- Resists extreme heat and pressure.
- Protects against wear and corrosion.
- Low pour point for versatility.
- Total Drive Line universal application.
- For transmissions and hypoid differentials.
- For use in passenger cars, vans and heavy trucks.

Search ID: PMXGO75140		
20 L	205 L	1000



Specifications
API GL-4 / GL-5 / MT-1; MIL-L-2105D / MIL-PRF-2105E, SAE J2360;
Scania STO 1:0 / 2:0 A;
ZF TE-ML 05A / 07A / 12B / 12N / 16F / 19C / 21A



GEARBOX OIL 75W-80 GL-4+

PMX Gearbox Oil 75W-80 GL-4+ - Multi-vehicle manual transmission fluid, based on high-quality base oils:

- Proven European and Asian synchronisers performance.
- Superior gear and bearing protection.
- Excellent cleanliness and corrosion protection.
- Reliable performance in low temperatures.
- Suitable for manual and Dry-DCT transmissions.

Search ID: PMXGO78GL4		
20 L	205 L	1000



Specifications
API GL-4; BMW MTF LT-2 / LT-3 / LT-4; Fiat 9.55550-MZ1/-MZ2 /-MZ6/-MZ7; Ford WSS/WSD M2C200-E1/-D2/-C / ESD-M2C186-A; GM GMW16612 / 1940004 / 19259104; GM 1940182 / 1940764 / 1940768; Honda MTF -II / -III; MB 235.10; Nissan MT-XZ / -XZ TL (JR Type); PSA B71 2310/ 2315/ 2316/ 2317 / 2330/ 9730 A8/AG; Renault DC4 / DW5; Special gear oil; MTF 94 / BOT 350 M3; Tranself NEJ/NFP/NFX/TRJ/TRP/TRT/TRX/TRZ; Volvo 97308 / 97309; VW G 009 317 / 052 171 / 052 178 / 052 512; VW G 052 527 / 052 549 / 052 726; VW G 50 / 055 512 / 060 726 / 070 726

PMX HYDRA

Hydraulic oil.
For Heavy Duty vehicles and machines.

PMX

HYDRA 32 BIO

PMX Hydra 32 BIO - High quality hydraulic oil:

- Good resistance to high temperatures and oxidation.
- Very good protection against wear, corrosion and foam.
- Very low pour point.
- Very good anti-wear properties.
- Good water separation properties.
- High and stable viscosity index.

Search ID:
PMXH32BIO

20 L	205 L	1000
------	-------	------



Specifications

EU ECOLABEL; Swedish Standart SS 15 54 34; ISO 15380 HEES;
OECD 301 B > 70%

PMX

HYDRA 32 HLP

PMX Hydra 32 HLP - Hydraulic oil:

- Good resistance to high temperatures and oxidation.
- Very good protection against wear, corrosion and foam.
- Low pour point.
- Very good anti-wear properties.
- Good properties with synthetic gaskets and seals.
- High and stable viscosity index.

Search ID:
PMX32HP

20 L	205 L	1000
------	-------	------



Specifications

ISO VG 32; ISO 11158 HM; DIN 51 524 part 2 HM/HLP

PMX

HYDRA 32 HVLP

PMX Hydra 32 HVLP - Hydraulic oil:

- Good resistance to high temperatures and oxidation.
- Very good protection against wear, corrosion and foam.
- Low Pour Point.
- Very good anti-wear properties.
- Good properties with synthetic gaskets and seals.
- High and stable viscosity index.

Search ID:
PMX32HVLP

20 L	205 L	1000
------	-------	------



Specifications

ISO VG 32; ISO 1158 HV; DIN 51 524 part 3 HVLP



HYDRA 32 SZF

PMX Hydra 32 SZF - Zinc free hydraulic oil:

- Good resistance to high temperatures and oxidation.
- Very good protection against wear, corrosion and foam.
- Low pour point.
- Very good anti-wear properties.
- Good properties with synthetic gaskets and seals.
- High and stable viscosity index.

Search ID:
PMX32SZF

20 L 205 L 1000



Specifications

ISO VG 32; ISO 1158 HV; DIN 51 524 part 3 HVLP



HYDRA 46 BIO

PMX Hydra 46 BIO - High quality hydraulic oil:

- Good resistance to high temperatures and oxidation.
- Very good protection against wear, corrosion and foam.
- Very low pour point.
- Very good anti-wear properties.
- Good water separation properties.
- High and stable viscosity index.

Search ID:
PMXH46BIO

20 L 205 L 1000



Specifications

ISO VG 46; EU Ecolabel; Swedish Standard SS 15 54 34; ISO 15380 HEES; Biodegradability according OECD 301 B >70%



HYDRA 46 HLP

PMX Hydra 46 HLP - Heavy Duty hydraulic oil:

- Good resistance to high temperatures and oxidation.
- Very good protection against foam/air in the oil.
- Low pour point.
- Ensure optimal control properties in controls and propulsion.
- Best under stable temperature environment.
- Stable viscosity index.

Search ID:
PMX46HP

20 L 205 L 1000



Specifications

ISO VG 46; ISO 11158 HM; DIN 51 524 part 2 HM/HLP



HYDRA 46 HVLP

PMX Hydra 46 HVLP - High quality hydraulic oil:

- Good resistance to high temperatures and oxidation.
- Very good protection against wear, corrosion and foam.
- Very low pour point.
- Very good anti-wear properties.
- Good water separation properties.
- High and stable viscosity index.

Search ID:
PMX46HVLP

20 L 205 L 1000



Specifications

ISO VG 46; ISO 1158 HV; DIN 51 524 part 3 HVLP



HYDRA 46 SZF

PMX Hydra 46 SZF - High quality zinc free hydraulic oil:

- Good resistance to high temperatures and oxidation.
- Very good protection against wear, corrosion and foam.
- Low pour point.
- Very good anti-wear properties.
- Good properties with synthetic gaskets and seals.
- High and stable viscosity index.

Search ID:
PMXZF46HV

20 L	205 L	1000
------	-------	------



Specifications

ISO VG 46; ISO 1158 HV; DIN 51 524 part 3 HVLP



HYDRA 15 HVLP

PMX Hydra 15 HVLP - High quality hydraulic oil:

- Good resistance to high temperatures and oxidation.
- Very good protection against wear, corrosion and foam.
- Very low pour point.
- Very good anti-wear properties.
- Good water separation properties.
- High and stable viscosity index.

Search ID:
PMX15HV

1 L	5 L	20 L
-----	-----	------

205 L	1000
-------	------



Specifications

ISO VG 15; AFNOR NF E 48-603 HV; ASTM D 6158 HV; DIN 51524-3 HVLP; ISO 11158 HV / 6743-4 HV



HYDRA 22 HVLP

PMX Hydra 22 HVLP - High quality hydraulic oil:

- Good resistance to high temperatures and oxidation.
- Very good protection against wear, corrosion and foam.
- Very low pour point.
- Very good anti-wear properties.
- Good water separation properties.
- High and stable viscosity index.

Search ID:
PMX22HV

1 L	20 L	205 L
-----	------	-------

1000



Spekifikationer

ISO VG 22; AFNOR NF E 48-603 HV; ASTM D 6158 HV; DIN 51524-3 HVLP; ISO 11158 HV / 6743-4 HV



HYDRA 100 HVLP

PMX Hydra 100 HVLP - High quality hydraulic oil:

- Good resistance to high temperatures and oxidation.
- Very good protection against wear, corrosion and foam.
- Very low pour point.
- Very good anti-wear properties.
- Good water separation properties.
- High and stable viscosity index.

Search ID:
PMX100HV

20 L	205 L	1000
------	-------	------



Specifications

ISO VG 100; AFNOR NF E 48-603 HV; ASTM D 6158 HV; DIN 51524-3 HVLP; ISO 11158 HV / 6743-4 HV

PMX CONVERSION

ARTICLE NO.	PMX COMPLETE RANGE	MPM	CASTROL
PMX89LS	PMX 80W-90 LS	10001LS Gear Oil SAE 90 GL-5 Mineral Limited Slip	Axle Limited Slip 80W-90
PMX140G5	PMX 85W-140 G5	14001 Gear Oil 85W-140 GL-5 Mineral Hypoid Oil	Axle EPX 85W-140
PMXAD3	PMX ATF Dexron III	*	Transmax Dex/Merc
PMXGO75140	PMX Gearbox Oil 75W-140	18000TR Gear Oil 75W-140 Premium Synthetic Truck	
PMXGO78GL4	PMX Gearbox Oil 75W-80 GL-4+	*	Transmax Manual Long Life 75W-80
PMXGO79G45	PMX Gearbox Oil 75W-90 GL-4/5	18000G Gearbox Oil 75W-90 GL-3/4/5 Premium Synthetic TDL	
PMXGO79G5S	PMX Gearbox Oil 75W-90 GL-5 LS	*	Transmax Limited Slip 75W-90
PMX100HV	PMX Hydra 100 HVLP	*	Hyspin AWS 100
PMX15HV	PMX Hydra 15 HVLP	33000 Hydraulic Oil HVI 15	Hyspin AWS 15
PMX22HV	PMX Hydra 22 HVLP	33000A Hydraulic Oil HVI 22	Hyspin AWS 22
PMXH32BIO	PMX Hydra 32 BIO	32000BIO Biodegradable Hydraulic Oil HVI 32	
PMX32HP	PMX Hydra 32 HLP	32000BG Hydraulic Oil HLP 32	Hyspin AWS 32
PMX32HVLP	PMX Hydra 32 HVLP	32000 Hydraulic Oil HVI 32	Hyspin AWH-M 32
PMX32SZF	PMX Hydra 32 SZF	*	Hyspin HVI 32
PMXH46BIO	PMX Hydra 46 BIO	30000BIO Biodegradable Hydraulic Oil HVI 46	
PMX46HP	PMX Hydra 46 HLP	30000BG Hydraulic Oil HLP 46	Hyspin AWS 46
PMX46HVLP	PMX Hydra 46 HVLP	30000 Hydraulic Oil HVI 46	Hyspin AWH-M 46
PMXZF46HV	PMX Hydra 46 SZF	*	Hyspin HVI 46

* Manufacturer has no product

	MOBIL	TOTAL	VALVOLINE	FUCHS	NESTE
	Delvac Modern Limited Slip Axle Oil 80W-90	Dynatrans DA 80W-90	HD Axle Oil Pro 80w-90 LS	TITAN Gearway LS5 80W-90	Axle LS 80W-90
	HD Plus Gear Oil 85W-140	Traxium Axle 7 85W-140	HD Axle 85W-140	TITAN Supergear MC 80W-140	Axle 80W-140
	Mobil 1 Synthetic ATF	Fluidmatic D3	Heavy Duty ATF	TITAN ATF 5500	ATF-X
	Delvac™ 1Gear Oil 75W-140	Traxium Axle 8 FE 75W-140	Heavy Duty Axle Oil 75W-140	TITAN Supergear Synth 75W-140	Pro Axle 75W-140
	Delvac 1 Transmission Fluid 75W-80	Trax	HD Gear Oil 75w-80	TITAN CYTRAC MAT SAE 75W-80	Pro Gear 75W-80
	Delvac 1 Gear Oil 75W-90	Traxium Gear 8 75W-80	HD TDL Pro 75W-90	TITAN Cytrac RR 75W-90	Pro Gear 75W-90
	*	*	Heavy Duty Axle Oil 75W-90 LS	TITAN Supergear Synt LS 75W-90	Pro Axle TDL 75W-90
	The Mobil SHC 527	Equivis ZS 100	Ultramax HVLP 100 EEE	*	*
	*	Equivis ZS 15	Ultramax HVLP 15 EEE	B 15 HVI	Hydraulic 15 Super
	Univis™ N 22	Equivis ZS 22	Ultramax HVLP 22 EEE		Hydraulic 22 Super
	EAL 224H	Biohydran TMP 32	*	PLANTOSYN SE 32 HP	Biohydraulic SE 32
	DTE 24	Azolla ZS 32	Ultramax HLP 32	RENOLIN B 10 VG 32	Hydraulic HLP 32
	The Mobil SHC 32	Equivis ZS 32	Ultramax HVLP 32	B 32 HVI	Hydraulic 32
	DTE 10 Excel 32	Equivis AF 32	*	ZAF 32 MC	Hydraulic HLP ZFX 32
	EAL 224H	Biohydran TMP 46	Ultramax Bio-46	PLANTOSYN SE 46 HP	Biohydraulic SE 46
	DTE 25	Azolla ZS 46	Ultramax HLP 46	RENOLIN B 10 VG 46	Hydraulic HLP 46
	The Mobil SHC 46	Equivis ZS 46	Ultramax HVLP 46	B 46 HVI	Hydraulic 46
	DTE 10 Excel 46	Equivis AF 46	*	ZAF 46 MC	Hydraulic HLP ZFX 46

PMX CONVERSION

ARTICLE NO.	PMX COMPLETE RANGE	MPM	CASTROL
PMXM1030S	PMX Multi 10W-30 STOU	35000 STOU 10W-30 GL-4 Multigrac Mineral	Transmax AGRI MP PLUS 10W-30 **
PMXM1040S	PMX Multi 10W-40 STOU	35000A STOU 10W-40 GL-4 Multigrac Semi Synthetic	Transmax Agri MP Plus 10W-40 **
PMXT13EHPFE	PMX Truck 10W-30 EHP FE	04000AB Motor Oil 10W-30 Premium Synthetic EHPD Truck FE	Vecton Long Drain 10W-30 E6/E9
PMXT1040E7	PMX Truck 10W-40 E7	04000A Motor Oil 10W-40 Super High Performance Diesel Truck	CRB TURBOMAX 10W-40 E4/E7
PMXT14LDE11	PMX Truck 10W-40 LD E11	05000AD Motor Oil 10W-40 Premium Synthetic Long Drain Plus	VECTON Long Drain 10W-40 E6/E9
PMXT1540E7	PMX Truck 15W-40 E7	03000D Motor Oil 15W-40 Super High Performance Diesel	CRB MULTI 15W-40 CI-4/E7
PMXT24EHP	PMX Truck 15W-40 EHP	04000AC Motor Oil 15W-40 Premium Synthetic EHPD Truck	VECTON 15W-40 CK-4/E9
PMXT53LFE11	PMX Truck 5W-30 LD FE E11	05000LE Motor Oil 5W-30 Premium Synthetic HDD LE Truck	VECTON Long Drain 5W-30 E6/E9
PMXT53V	PMX Truck 5W-30 VDS-5	*	VECTON LONG DRAIN 5W-30 FA-4/F8
PMXTGO71	PMX Truck Gear Oil 75W-140	18000TR Gear Oil 75W-140 Premium Synthetic Truck	Transmax Axle Long Life 75W-140
PMXTG79G5	PMX Truck Gear Oil 75W-90 GL-5	18000G Gearbox Oil 75W-90 GL-3/4/5 Premium Synthetic TDL	Transmax Universal Long Life 75W-90
PMXTG79G5LS	PMX Truck Gear Oil 75W-90 GL-5 LS	*	Transmax Limited Slip 75W-90
PMXTGO89G	PMX Truck Gear Oil 80W-90 GL-5	*	Transmax Axle EPX 80W-90
PMXTGOS9G	PMX Truck Gear Oil SAE 90 GL-5 LS	10001LS Gear Oil SAE 90 GL-5 Mineral Limited Slip	
PMXWBU	PMX WB UTTO	37000 UTTO GL-4 Mineral	Transmax Agri Trans Plus 80W
PMXWBUS	PMX WB UTTO SYN	37000S UTTO GL-4 Premium Synthetic	*
PMXWBUT4	PMX WB UTTO TO-4	*	*

* Manufacturer has no product

	MOBIL	TOTAL	VALVOLINE	FUCHS	NESTE
	*	Multiagri Super 10w-30	STOU 10W-30	AGRIFARM STOU MC SAE 10W-30	Farm Universal 10W-30
	*	Multiagri Pro-Tec 10w-40	STOU 10w-40	AGRIFARM STOU MC SAE 10W-40	*
	Delvac 1300 Super 10w-30	Rubia Optima 1100 FE 10W-30	AllFleet Superior LE 10W-30	TITAN CARGO SAE 10W-30	Turbo+ NEX 10W-30
	*	Rubia TIR 8600 10W-40	AllFleet Extreme 10W-40	TITAN TRUCK PLUS SAE 10W-40	Turbo LXE 10W-40
	Delvac XHP ESP 10W-40	Rubia Optima 3500 10W-40	AllFleet Superior LE-X 10W-40	TITAN CARGO MAXX II SAE 10W-40	Turbo+ NEX 10W-40
	Delvac MX F2 15w-40	Rubia Optima 1100 15W-40	AllFleet Extra 15w-40	TITAN UNIVERSAL HD SAE 15W-40	Turbo LXE 15W-40
	Delvac 1300 Super 15W-40	Rubia Optima 1100 15W-40	AllFleet Superior LE 15w-40	TITAN CARGO SAE 15W-40	Turbo+ VPX 15W-40
	Delvac 1 5W-30 Advanced Synthetic diesel oil	Rubia Optima 3500 FE 5W-30	ProFleet LS Plus 5W-30	TITAN CARGO MAXX II SAE 5W-30	Turbo+ LSA S4 5W-30
	Delvac 1™ Advanced Fuel Economy 5W-30	Rubia Optima 4100 XFE 5W-30	ProFleet LS-F 5W-30	TITAN CARGO PRO 228.61 SAE 5W-30	Turbo+ FA-4 5W-30
	*	Traxium Axle 8 FE 75W-140	Heavy Duty Axle Oil 75W-140	TITAN SUPERGEAR SYNTH SAE 75W-140	Pro Axle 75W-140
	Delvac 1 Gear Oil 75W-90	Traxium Gear 8 75W-80		TITAN CYTRAC TD SAE 75W-90	Pro Axle 75W-90
	*	*	Heavy Duty Axle Oil 75W-90 LS	TITAN CYTRAC TD SAE 75W-90	
		Traxium Axle 7 80W-90	HD Axle Oil Pro 80w-90 LD	TITAN SUPERGEAR SAE 80W-90	Axle 80W-90
	Delvac Modern Limited Slip Axle Oil 80W-90	Dynatrans DA 80W-90	HD Axle Oil Pro 80w-90 LS	TITAN SUPERGEAR LS 80W-90	Axle LS 80W-90
	Mobilfluid 424	Dynatrans MPV	Valvoline UTTO	TITAN UTTO WB	Gear UTTO
		Dynatrans VX FE	UTTO WB2	AGRIFARM UTTO Pro 102	UTTO NEX WB2
	Mobiltrans HD 10W	Dynatrans ACX 10W	DT Transmission Oil 10W	TITAN UTTO TO-4 SAE 10W	Gear TO-4 10W

PMX